

Technical specifications

tessera® arran

Arran carpet tiles meet the requirements of EN 1307

Description	Tufted multi-height loop pile carpet tile	
Dimensions	50cm x 50cm (Other sizes available for special orders)	
Total thickness	7.0mm ± 10%	
Pile height	4.0mm ± 0.5mm	
Collection size	12 colourways, 4m ² per box	
Application	EN 1307	Class 33, Suitable for any type of heavy contract application
Pile composition	100% Invista Antron® Lumena polyamide	
Dye method	100% solution dyed	
Stitch density	202,960 per m ² ± 10%	
Pile weight	950 gsm ± 10%	
Total weight	4,465 gsm ± 10%	
Primary backing	Polyester/Polyamide	
Secondary backing	Modified bitumen and polyester fleece. Also available in SOFTbac® secondary backing	
Castor chair use	BS EN 985:2001	Minimum R value: ≥2.4 Overall R value: ≥ 2.9
Light fastness	BS EN ISO 105 B02	≥5
Dimensional stability	BS EN 986	≤0.2%
Impact sound reduction	ISO 140-8	23 dB
Creating Better Environments		
Renewable Electricity	All Tessera carpet tiles are manufactured using 100% electricity made from renewable sources	
Recycled Content	Arran contains 58% recycled content by weight	
Indoor Air Quality	Arran meets 01350 Indoor Air Quality standard	
Back to the Floor	Installation off cuts can be collected and recycled via Back to the Floor	
Ska	Arran meets Ska Rating criteria for M12 soft floor coverings in both office and retail schemes	
10 Guarantee	Arran carpet tiles are guaranteed for 10 years under heavy contract conditions (15 years guaranteed with SOFTbac®) provided that they have been professionally fitted by a recognised contractor and regularly maintained in accordance with the Forbo requirements currently in force.	
Installation method	Monolithic, quarter turn or tessellated	

Arran carpet tiles meet the requirements of EN 14041



Reaction to fire	EN 13501-1	B _{fl} -s1
Slip resistance	EN 13893	DS: ≥0.30
Electrical resistance	BS ISO 10965 & EN1815	<1 x 10 ⁹ Ω: Static dissipative. Body voltage: Pass (< 2kV) Lifetime protection through the use of permanent anti-static yarn and backing

BREEAM ratings

Tessera Arran – Carpet Tiles (EN1307)

Building Type	Education	Healthcare	Multi Residential	Retail (Durability)	Retail (Fashion)	Meets Ska criteria
Office	B	A	B	B	A+	✓

SAMPLE SERVICE
0800 731 2369
samples.uk@forbo.com



Our recommended adhesive for our collection of Tessera carpet tiles is 542 Eurofix Tack plus. Please contact customer services for more information.

All Forbo Flooring Systems' sales organisations and manufacturing sites worldwide have certified Quality Management Systems in accordance with ISO 9001.

All Forbo Flooring Systems' manufacturing plants have certified Environmental Management Systems in accordance with ISO 14001.

Arran carpet tiles are manufactured in a facility certified to SA8000® and OHSAS 18001.

The Life Cycle Assessment (LCA) of Forbo Flooring Systems' products is documented in individual Environmental product declarations (EPD's) or local building rating schemes such as BREEAM.

Whilst Forbo Flooring UK Limited does its best to ensure that the contents of this specification are correct and accurate at the time of publication, to the fullest extent permitted by law, Forbo Flooring UK Limited makes no, and expressly disclaims all, guarantees of any kind, express or implied in respect of the information, content, materials or products displayed in this specification and does not represent that the information is accurate, complete or current.

www.forbo-flooring.co.uk

