technical specifications

Product Name Product Description

Pile Yarn Description 100% Solution Dyed Aquafil Econyl® Nylon (Polyamide-PA)

Tile Dimensions Pile Yarn Weight **Total Weight** Pile Height **Total Thickness**

Gauge/ends per 10cm Tufts per m2 / Pile Density

Backing Description

Wear Classification

Luxury Rating Class

Flammability

Thermal Resistance Castor Chair Rating

Hexapod

Static Loading **Dynamic Loading**

Body Voltage Test Colour Fastness To Light Colour Fastness To Shampoo

Sound Absorption Coefficient

Reduction in Impact Noise Reduction in Impact Noise at 1000Hz BS EN ISO 10140-3:2010 33.4dB

Alaska

Multilevel Loop

50 cm x 50 cm 800g/m² +/-10% 4200g/m² +/-10% 5.0mm +/-10% 7.5mm +/-10%

1/12th gauge 48 stitches 226,771/m² +/-10%

Accummen™, 75% recycled

BS EN 1307 Heavy Commercial Use Class 33

LC₂

Euroclass Bfl-s1

Tog Rating 0.56; ISO 8302: 0.081m2K/W BS EN 985 Pass - suitable for continuous use

BS ISO 10361: Method B:2000 3 to 4

BS 4939: 1987 (2003) Recovery >80% (24hrs)

BS ISO 2094: 1999 (2005) Loss <20% (1000 impacts)

BS ISO 6356:2000 <2kV

BS EN ISO 105 - B02 Minimum Grade 6 BS 1006:UK-TB: 1990 Minimum Grade 4-5

BS EN 354:2003

BS EN ISO 10140-3:2010 22dB

Number Of Tiles Per Box 20 (5m²)



For best results

we recommend

Monolithic



























nvironmental Profiles





Statement on level of emission of volatile substances in indoor of volatile substances in indoor air posing a toxic threat during inhaling - on a scale from A-(very low-emission) to C (high-



The Building Information Foundation, Finland. Certified building materials with low emission class M1

environmental information

- Burmatex products achieve either A or A+ across all the BREEAM defined building applications For specific rating, please refer to www.breeam.co.uk
- · Burmatex products qualify for SKA as they achieve one or more requested criteria
- · All Burmatex carpet/carpet tile/carpet plank ranges are made at its single UK manufacturing site
- Wherever possible, raw materials including yarn/fibre are sourced locally i.e. within 20 miles
- Over 75% of Burmatex Accummen[™] backing comes from recycled materials
- · Continuous assessment and improvement of manufacturing process to minimise use of raw materials/power · All manufacturing waste is recycled and all electricity used is from renewable resources
- · All Burmatex products are heavy contract with a 10 year guarantee for maximum useful life

Certified, Class A+: very-low VOC Emission

LEED® v4 - Burmatex products can contribute towards satisfying the following credits for LEED v4: NC-v4/CI-v4 MRc2/MRc3 (Building product disclosure and optimization - environmental product declarations), MRc3/MRc4 (Building product disclosure and optimization - sourcing of raw materials), EQc1 (Enhanced indoor air quality strategies), EQc2 (Low-emitting materials), EQc6 (Interior lighting - Option 2. Lighting quality (E - H)) and EQc9 (Acoustic Performance). Products are not reviewed under LEED. LEED credit requirements cover the performance of materials in aggregate, not the performance of individual products or brands. For more information on LEED, visit www.usgbc.org/contact

Burmatex Ltd Victoria Mills, The Green Ossett, West Yorkshire WF5 OAN **United Kingdom**

T +44 (0) 1924 262 525 F +44 (0) 1924 280 033

UK email: projects@burmatex.co.uk International email: international@burmatex.co.uk www.burmatex.co.uk

Burmatex reserves the right to improve the specification of all products without prior notification, E&OE Burmatex carpets, carpet tiles and carpet planks should be installed and used in full accordance with instructions at www.burmatex.co.uk and recognised trade standards. Orders are subject to Burmatex terms and conditions of sale See: www.burmatex.co.uk

LRV values for **alaska**

Product code tiles	Product colour name	CIE Y	CIE L
22201	ice	14.80	45.36
22202	ridge	10.09	38.00
22203	point	7.97	33.91
22204	north	6.57	30.80
22205	moose	3.24	20.98
22206	anchor	2.35	17.23
22207	creek	2.73	18.91
22208	lake	7.10	32.04
22209	husky	14.79	45.35
22210	wolf	7.41	32.71
22211	spruce	6.49	30.63
22212	valley	3.83	23.09