

FINETT ACCENT

Level of use

EN 1307

class 33 heavy duty

Emission tested

acc. to DIBt-principles
acc. to CRI-principles

abZ-Nr.: Z-156.601-401
Green Label Plus 2655

Health safety

Environmental label RAL-UZ 128

DER BLAUE ENGEL
Contract No. 19064

Wear layer

100 % polyamide **dorix**

Back

Nonwoven with PP-mesh

Total thickness

ISO 1765

6,5 mm

Total weight

ISO 8543

1500 g/m²

Fibre weight

750 g/m²

Wear layer weight

EN 984

700 g/m²

Dimensions

roll width 200 cm | roll length 25-35 rm

Fire rating

EN 13501-1

B_{fl}-s1

Impact sound insulation

ISO 10140

23 dB

Level of sound absorption

ISO 354

Freq. Hz	125	250	500	1000	2000	4000
α_s	0,01	0,01	0,09	0,18	0,41	0,63

Colour fastness to light

ISO 105-B02

6-7

Thermal resistance

ISO 8302

0,13 m² K/W
suitable for underfloor heating

Anti-Static

ISO 6356

≤ 0,5 kV

Resistance to earth

EN 61340-4-1 (glued conductively)

≤ 1 x 10⁸ Ω (geometric mean)

Special colours

> 1000 m²

Installation

DIN 18365

For the correct installation of our textile floorings use only ultra low emission adhesives, free of low-, middle- and high boiling solvents and with very high shear strength (> 2 N/mm², in accordance with EN 14293).

Subject to improvements and usual colour deviations.



heavy duty



No repeat

FINETT FLEX

DIE ARBEIT WIRD LEICHTER

Date of issue 04.2016 | Revision H



Mitglied der



DGNB

Deutsche Gesellschaft für Nachhaltiges Bauen e.V.
German Sustainable Building Council

